

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) An image sensor comprising:
 - (a) a plurality of pixels;
 - (b) a color filter pattern spanning at least a portion of the pixels, wherein the color filter pattern forms a plurality of color filter kernels having the same colors in a predetermined arrangement wherein the kernels are arranged in at least two different uniformly distributed sets; and
 - (c) a mechanism for controlling integration time of the ~~pixels~~ different sets of kernels according to their spatial location, wherein the integration time is different for each set of the kernels.~~of the plurality of pixels is spatially variant in a pattern that is correlated with the color filter array kernel.~~
2. (Original) The image sensor as in claim 1, wherein the color filter pattern is a Bayer color filter pattern.
3. (Original) The image sensor as in claim 1, wherein the color filter pattern is a 2x2 kernel.
4. (Original) The image sensor as in claim 3, wherein the integration time pattern is an alternating pattern of two lines at one integration time and adjacent two lines at a second integration time.
5. (Original) The image sensor as in claim 3, wherein the integration time for a first set of 2x2 pixels associated with a first kernel is at a first integration time, and the integration time of adjacent 2x2 kernels in the same set of two lines at a second integration time.
6. (Original) The image sensor as in claim 5, wherein the integration time pattern of adjacent two lines groups is offset by two pixels.
7. (Cancelled)

8. (Original) An image sensor comprising:

(a) a plurality of pixels arranged in an array of rows and columns;

and

(b) a readout mechanism that provides a series of output signal values associated with a row sync signal with a number of data signal values corresponding to a number of pixels in a row or desired portion of a row; wherein the output signal values have signals that are generated from pixels within at least two physically separate rows within the array.

9. (Currently Amended) A camera comprising:

(a) an image sensor comprising:

(a1) a plurality of pixels;

(a2b) a color filter pattern spanning at least a portion of the pixels, wherein the color filter pattern forms a plurality of color filter kernels having the same colors in a predetermined arrangement wherein the kernels are arranged in at least two different uniformly distributed sets; and

(a3c) a mechanism for controlling integration time of the pixels different sets of kernels according to their spatial location, wherein the integration time is different for each set of the kernels.~~of the plurality of pixels is spatially variant in a pattern that is correlated with the color filter array kernel.~~

10. (Original) The camera as in claim 9, wherein the color filter pattern is a Bayer color filter pattern.

11. (Original) The camera as in claim 9, wherein the color filter pattern is a 2x2 kernel.

12. (Original) The camera as in claim 11, wherein the integration time pattern is an alternating pattern of two lines at one integration time and adjacent two lines at a second integration time.

13. (Original) The camera as in claim 11, wherein the integration time for a first set of 2x2 pixels associated with a first kernel is at a first

integration time, and the integration time of adjacent 2x2 kernels in the same set of two lines at a second integration time.

14. (Original) The camera as in claim 13, wherein the integration time pattern of adjacent two lines groups is offset by two pixels.

15. (Cancelled)

16. (Original) The camera as in claim 9 further comprising a mechanism that reads out at least a subset of the plurality of pixels and uses the signal values obtained from the readout to determine the integration times of the plurality of pixels.

17. (Original) A camera comprising:

(a) an image sensor comprising:

(b) a plurality of pixels arranged in an array of rows and columns;

and

(c) a readout mechanism that provides a series of output signal values associated with a row sync signal with a number of data signal values corresponding to a number of pixels in a row or desired portion of a row; wherein the output signal values have signals that are generated from pixels within at least two physically separate rows within the array.

18. (Currently Amended) The camera as in claim 17, wherein the data values are reconstructed in ~~the camera~~ a camera memory.